# **DATA SHEET**



# soni ELEMENT

- ► soni ELEMENT is a range of charming acoustic elements for effective noise absorption and sound-conditioning. They consist of a white polyester non-woven, optionally laminated with a decorative felt material in modern trend colors. Designed for elements, the noise absorbers are available in different sizes and a wide variety of shapes – for customized room decoration in line with your individual design concept and ideas.
- ► The installation of **soni ELEMENT** improves speech intelligibility, resulting in a more pleasant atmosphere and a lower noise level in day-care centers, kindergartens and schools etc.



#### TECHNICAL DATA

TECHNICAE DAIA			
FLAMMABILITY	► DIN EN 13501-1: C-S2, d0* (Colour variants)		
	►DIN 4102, tested according to B1 (flame-retardant) (colour: white)		
	Fulfills the strict fire safety standard for the automotive industry		
	(FMVSS 302, DIN 75 200)		
	► ISO 3795, burning rate < 100 mm/min		
TEMPERATURE RESISTANCE	>-30°C to +100°C		
THERMAL CONDUCTIVITY / EN 12667	►≤ 0.037 W/(m·K) at 10°C		
DIMENSION CHANGE WHEN EXPOSED TO HEAT	►at temperatures above 100°C: approx. ± 10%		

<sup>\*</sup>glued on plaster board with soni SPECIAL ADHESIVE, or fixed with soni VELCRO tape.

#### **BENEFITS**

- ► Good sound absorption values
- ► Free of mineral fibers, physiologically safe, no emission of formaldehyde
- ► Excellent flammability characteristics
- ► High durability and good shape stability / High ageing stability

### **ADVICE**

### **FIXATION OPTIONS**

- ► There might be minimal color variations between different lots
- Soni SPECIAL ADHESIVE
- Soni RING HANGER


















2. Remove protective film and stick Velcro tape with adhesive

backing to the wall.



#### **REVERBERATION ROOM**

## ► Based on DIN EN ISO 354



# FIXATION USING SELF-ADHESIVE VELCRO TAPE



1. Cut off the Velcro tape to the required length.




3. Press element on the Velcro tape

Details and values given in this leaflet are average values and have been compiled with care. They are not binding, however, and Cellofoam International GmbH & Co. KG disclaims any liability for any damages and detriments, also in connection with any third party's rights. The information given does not release the buyers from making the necessary experiments and tests themselves. Subject to technical changes. For updates please go to our website.

Cellofoam International GmbH & Co. KG P: +49 7351 340 28 61 sales@soniflex.de / www.soniflex.de

# VERSION 02/22

Distribution partner for Switzerland: P: +41 44 377 60 50 einkauf@soniflex.ch / www.soniflex.ch





DIMENSIONS				
PRODUCT	DIMENSION [mm]	GRAMMAGE PER ELEMENT	COLOUR SAMPLES	
SONİ ELEMENT LEO	Large: 971 X 603 X 50* Small: 587 X 364 X 50*	Large: 550 g Small: 170 g ± 10 %		
SONI ELEMENT BRUNO	Large: 926 X 558 X 50* Small: 518 X 312 X 50*	Large: 560 g Small: 240 g ± 10 %		
SONI ELEMENT FRED	Large: 866 X 558 X 50* Small: 521 X 336 X 50*	Large: 420 g Small: 180 g ± 10 %		
SONI ELEMENT BUTTERFLY	Large: 853 X 569 X 50* Small: 512 X 341 X 50*	Large: 360 g Small: 130 g ± 10 %		
SONI ELEMENT FLORA	Large: 602 X 554 X 50* Small: 407 X 407 X 50*	Large: 360 g Small: 150 g ± 10 %		
SONI ELEMENT CLOUD	Large: 989 X 575 X 50* Small: 533 X 308 X 50*	Large: 570 g Small: 160 g ± 10 %		
SONI ELEMENT STAR	Large: 600 X 571 X 50* Small: 360 X 343 X 50*	Large: 207 g Small: 70 g ± 10 %		
SONİ ELEMENT TRAIN	Lok: 780 x 570 x 50* W: 406 x 427 x 50*	Lok: 465 g W2: 186 g ± 10 %		

<sup>\*</sup>Thickness tolerance / EN ISO 9073-2: 10%